



Electric Steam Generator

Features

1. Automatic pressure protection device, automatically stops heating when the set pressure is reached.
2. Water shortage alarm buzzer;
3. Spring-type safety valve (over pressure protection, when boiler steam pressure exceeds the set upper limit. When the pressure is limited, the safety valve starts to release steam to reduce the pressure to ensure safe operation.Complete).
4. Stainless steel water tank, high temperature resistant water pump.
5. Heat insulation device: Double-layer sealed fiber-glass heat insulation device to prevent heat loss, save electricity.
6. Heating tube: #304 stainless steel with thicker diameter, reduce the heat load on the surface of the heating tube, extend the service life of the heating tube.



电加热蒸汽发生器

机器特性

- 1、自动压力保护装置，达到设定压力时自动停止加热；
- 2、缺水报警蜂鸣器；
- 3、弹簧式安全阀（超压保护，当锅炉蒸汽压力超过设定的上限压力时，安全阀启动释放出蒸汽使压力降低保证运行安全）；
- 4、不锈钢水箱，耐高温水泵；
- 5、隔热装置：双层密封式玻璃纤维隔热装置，防止热力散失，省电；
- 6、发热管：#304不锈钢加粗管径，降低发热管表面热负荷，延长发热管使用寿命。



Parameters 机器参数

Model 产品型号	GOA-3KW	GOA-6KW	GOA-9KW	GOA-12KW	GOA-18KW	GOA-24KW	GOA-36KW	GOA-48KW	GOA-72KW
Heating Tube Power 发热管功率	3kW	6kW	9kW	12kW	18kW	24kW	36kW	48kW	72kW
Water Pump Power 水泵功率	0.8kW				1.2kW				
Voltage 电压	AC 220V/50Hz				3P 380V/50Hz				
Rated Evapor at ion Capacity 额定蒸发量	4kg/h	8kg/h	12kg/h	16kg/h	25kg/h	32kg/h	50kg/h	66kg/h	100kg/h
Steam Pressure 蒸汽压力	0.4Mpa				0.7Mpa				
Steam Temperature 蒸汽温度	151°C	151°C	151°C	151°C	151°C	151°C	170°C	170°C	170°C
Water Boiler Capacity 炉胆水容积	16L	16L	24L	24L	29L	29L	29L	29L	29L
Water Inlet Diameter 给水入口口径	15mm	15mm	15mm	15mm	15mm	15mm	15mm	15mm	15mm
Steam Outlet Diameter 蒸汽出口口径	15mm	15mm	15mm	15mm	15mm	15mm	15mm	15mm	15mm
Drain Valve Diameter 排污阀口径	15mm	15mm	15mm	15mm	15mm	15mm	15mm	15mm	15mm
Safety Valve Diameter 安全阀口径	15mm	15mm	15mm	15mm	15mm	15mm	15mm	15mm	15mm
Machine Size 机器外形尺寸	600×440×880mm	720×500×980mm	800×520×1080mm		800×570×1100mm		850×680×1230mm		840×960×1340mm