



High-speed Computerized Lock Stitch Multi-needle Quilting Machine

Features

- Adjustable speed in computer control at range of 100-1000 rpm, and the stitch step is 2-12mm.
- Needle rows are driven by servo motor, main shaft adopts frequency conversion control.
- Saddle are made by aluminum alloy high rigid structure. The fabric support stand are separate from saddle in order to reduce the operating load of saddle motor.
- Dual clutch device, front and rear rollers is better synchronized.
- High-precision and high rigidity ball screw driving.
- 360 degree freely make any quilting pattern.
- Automatic thread-break detection function.
- Infrared sensor offer safety operation.
- Stable working, low noise, high precision, low thread-break and easy to operate.

Application

It is widely used for quilting high-quality garments, bedding covers, textile, leather, shoes, cap, bags, vanity, gloves, sleeping bag, seat cover and wall decoration etc.

高速电脑有梭多针绗缝机

机器特性

- 电脑可调节速度100-1000转/分钟，针步调节2-12mm。
- 排运动采用伺服驱动方式，主轴采用变频控制。
- 鞍架采用绗缝机的高刚性设计，底面布支架采用与鞍架分离的结构，有效减少鞍架电机的负载。
- 双离合装置，有效解决前后罗拉同步问题。
- 采用高精度、高刚性进口丝杆。
- 360度任意绗缝和无限次独立花样跨步绗缝。
- 面线断线自动停机功能。
- 红外线感应使操作更安全。
- 机器运行平稳，噪声小，精度高，断线率低、操作简易。

适用范围

用于生产服装、床上用品、纺织品、皮革、鞋、帽、手套、箱包、睡袋、手袋、沙发、坐垫、墙壁装饰品等。



Parameters 机器参数

Model 型号	64 Series		80 Series		96 Series		128 Series
	64-2-3	64-3-4/4.5/ 5/6	80-2-3	80-3-4/4.5/ 5/6	96-2-3	96-3-4/4.5/ 5/6	128-2-316
Dimension (L×W×H) 主机尺寸 (长×宽×高)	3800×1200×1800mm		4400×1200×1800mm		4800×1200×1800mm		5700×1200×1800mm
Quilting width 绗缝宽度	1650mm		2000mm		2450mm		3300mm
The number of needle rows 针排数	2	3	2	3	2	3	2/3
Space between needle rows 针排距	3"	3"+1"/ 1.5"/2"/3"	3"+1"/ 1.5"/2"/3"	3"+1"/ 1.5"/2"/3"	3"	3"+1"/ 1.5"/2*/3"	3"/3+3
Space between needle 针距	25.4mm	19.05mm 25.4mm	25.4mm				
X-axis travel X行程	203.2mm	228.6/228.6/ 304.8mm	203.2mm	304.8mm	254mm	304.8mm	254/304.8mm
Thickness of quilting 绗缝厚度	25mm						
Stitch length 步长	2-12mm						
Production speed (m/hour) 生产速度 (米/时)	20-160						
Shuttle model 梭子型号	7#/10#						
Needle model 机针型号	14#, 16#, 19#						
Quilting speed (r/min) 主轴转速 (转/分钟)	100-1000						
Voltage (AC) 电压 (AC)	3P 380V / AC 220V						
Total power 功率	3.5kW				5.5kW		7.5kW
Gross weight 全机重量	3300kg		3800kg		4500kg		5300kg

Customized model are available to meet client's various needs / 可按客户需求订做特殊机型



Tianjin Getonagain Technology Co.,Ltd

Address: No.1-108, Haibin Commercial Center, Zhaoxia Street, Baodi District, Tianjin, China Tel: +86 22-2252 6200
 Email: sales@getonagain.com www.getonagain.com
 Branch Office: India | Bangladesh | Pakistan | Vietnam | Germany | France | Mexico |

天津市再登科技有限公司

地址: 天津市宝坻区朝霞街道海滨商贸中心1-108 400-166-8581

东莞分公司: 东莞市厚街镇莞太路桥头路段西412号
 山西分公司: 山西转型综合改革示范区学府产业园长治路227号高新国际A座1101室
 再登科技(香港)有限公司: 香港九龍新蒲崗大有街1號勤達中心20樓1-5室
 中国台湾办事处: 臺灣新北市三重區重新路5段609巷20號5樓之4