



Computerized Single-color Single Roll Quilting and Embroidery Machine

单色单幅电脑绗绣机



Features

- Automatic Quilting Embroidery Control System, equipped with 10.4 inches Touch Screen Control Panel, user friendly window style display.
- Adopt small needle distance double-needle machine heads and the minimum needle distance is 50.8 mm (2 inches).
- With double needle bars independent control or manual control, free activation and locking; According to the production requirements, it can quickly and independently realize the switch of any needle spacing, and meet the requirements of efficient production of complex quilting and quilting embroidery.
- Automatic thread breakage detection, reducing labor intensity, Reduce downtime and increase continuous working time.
- Adopt large rotary hook, increase the capacity of bobbin, reduce the replacement frequency of bobbin, and further improve production efficiency.

Application

Suitable for Summer quilt, bed cover, mattress protective pad, Blankets, clothing, car seat covers, car mats, furniture upholstery, etc.

机器特性

- 自主绗绣控制系统，配10.4英寸触摸屏，窗口化界面；
- 采用小针距双针绗绣机头，最小针距为50.8mm（2英寸）；
- 双针杆独立控制或手动控制，自由激活、锁定；可根据生产要求自主快速实现针距任意隔头的切换，满足复杂组合绗缝、绗绣花型的高效生产要求；
- 自动断线检测，降低人工劳动强度；减少停机率，增加持续工作时间；
- 采用大旋梭，底线容量增加，减少底线更换频率，进一步提高生产效率。

适用范围

夏凉被、床罩、床垫保护罩、毯子，服装，汽车座椅套，汽车脚垫、家具软包等

Parameters 机器参数

Model 型号	GOAQE-NM-SFE-166-305×3300-B-2"CN (50.8) -VR2-NA-3P380	
Heads 头数	33	25
Needles 针数	66	50
Needle Distance 针距	50.8mm	67.5mm
Needle length 针迹长度	0.1-12.7mm	0.1-12.7mm
Needle Distance(First to Last) 落针尺寸	3302mm	3307mm
Max.speed 最高转速	1000rpm	1000rpm
Voltage 电压	3-phase 380V	3-phase 380V
Power 功率	4.5kW	4.5kW
Machine Size 机器尺寸	5300×1500×1940mm	5300×1500×1940mm