

Richpeace Automatic 4-Side Tape Binding Machine

RPAS-NM-B4E-1-2300×2500-SU-VR2-3P380



Application

Quilt, bed cover, blanket and other products automatic tape binding and automatic trademark sewing. It can be working together with the quit production line to the tape binding, or working independently after panel quilting.

Features

- 1. Richpeace independently developed electronic control system.
- 2. The circular conveyor belt with curved guide rail can complete the tape binding work automatically.
- 3. The automatic oil supply to the head reduces noise and extends the service life of the machine.
- 4. Lifting three synchronous presser foot ensures the beauty of the sewing stitches.
- 5. Automatic trimming function ensures the neat of the material before sewing and binding.
- 6. Automatic finishing device makes the end stitch in alignment, more accurate and beautiful.





Parameters

Stitch	Single-needle lock stitch
Corner Radius	80mm
Taping width	50mm (other sizes can be customized)
Max. speed of straight Sewing	2000 rpm
Max. Speed of Corner Sewing	1000 rpm
Stitch Length	4mm-6mm
Maximum size of quilt(L×W)	2.3m×2.5m
Quilting thickness	30mm(450 gsm, cotton)
Working speed	90-100 seconds /pc
Needle size	17-22#
Thread Trimming	Electromagnet trimming
Rotary Hook	2.5times hook
Power Supply	Three phase 380V
Air pressure	0.5MPa 3L/min
Installation size(L×W×H)	5500mm×5000mm×1650mm
Optional Device	Automatic trademark attaching device

TIANJIN RICHPEACE AI CO., LIMITED

Add: No.6 Baozhong Road, Baodi Economic Development Zone, Tianjin City, 301800 China Tel: +86-22-22533456 Fax: +86-22-22530075 Email: sales@richpeace.com

