

高频机

High-Frequency Machine



适用范围

汽车/摩托车脚垫压花、压标;吸塑包装;塑料热合;皮革压花。

机器特点

- •内置无极加热系统,温度0-300可调,辅助加热,缩短加工时间。
- 火花抑制器, 打火瞬间切断电流, 避免模具和材料烧坏。
- 自动过流保护装置,保护电子管和模具,提高使用寿命。
- •27.12MHZ国际标准高周波防护,机器性能稳定。
- •频率稳定器及屏蔽装置,大大降低干扰程度。
- •装配压力调节装置,可任意调节压力。
- 机头压力大, 脚感轻。
- 功率输出强劲,速度快、效率高。

Application

Embossing and Stamping for Car/Motorcycle Foot Mats, Blister Packaging, Plastic Heat Sealing and Leather Embossing.

Features

- Built-in stepless heating system with adjustable temperature from 0 to 300, providing auxiliary heating to shorten processing time.
- Spark suppressor: Instantly cuts off current during sparking to prevent damage to molds and materials.
- Automatic overcurrent protection device: Protects electronic tubes and molds, extending their service life.
- 27.12MHz international standard high-frequency protection ensures stable machine performance.
- Frequency stabilizer and shielding device significantly reduce interference levels.
- Equipped with a pressure adjustment device, allowing pressure to be adjusted freely
- · High head pressure with a light foot feel.
- · Powerful output, fast speed, and high efficiency.



高频机 High-Frequency Machine

机器参数 Parameters

型号 Model:	GOA-GP-D15KW-Y
功率: Power:	15kW
电源输入: Power Input:	25KVA
震荡管: Oscillation Tube:	8T85RB
驱动方式: Drive Method:	液压 Hydraulic
操作方式: Operation Method :	自动滑台 Automatic Sliding Table
最大压力: Maximum Pressure:	5T
工作时间: Working Hours :	0~10S可调 Adjustable from 0 to 10 seconds.
定盘尺寸: Fixed Plate Size:	可根据产品定制 Customizable according to product requirements
温度控制: Temperature Control:	0-300℃恒温可调 Adjustable Constant Temperature From 0 to 300°C
电压: Voltage:	3P 380V, 50Hz
机器尺寸: Machine Size:	3000×1850×1900mm
包装尺寸: Package Size:	3040×1880×2050mm
净/毛重: Net Weight:	1330/1450Kg

天津再登高智能制造有限公司

地址: 天津宝坻经济开发区天宝南环路3号B楼 邮箱: sales@getonagain.com 网址: www.GetonAgain.com **400-166-8581**

Tianjin GetonAgain SM Co., Ltd.

Address: Block B, No.3, Nan Huan Road, Economic Development Zone, Baodi, Tianjin, China. Email: sales@getonagain.com www.GetonAgain.com