

## 906电脑平绣机

## 906 Flat Embroidery Machine



### 适用范围

用于服装、箱包鞋帽、玩具、家居装饰和汽车内饰等产品的高级定制。

### 机器特点

- 全新电脑控制系统，15.6寸液晶触摸屏，屏幕显示刷新率:50ms/次，实时动态显示。友好的人机界面，触控灵活，存储量大，确保整机的高精度运行。
- 内存容量大，系统标准可存储1.3亿针。
- 花样旋转以及按比例放大和缩小：按照1%的单位增量放大缩小花样，范围从50%到200%，按照1°的单位增量旋转花样范围从0-89°。
- 断电保护功能：当电源突然断电时，机器可以自动搜索到断电前的暂停状态继续进行绣作。
- 可以旋转、缩放、复制、删除、编辑花样，可以实现软件限位，可选装晶片、绳绣、散珠和激光等特种绣功能。
- 进框/倒框键可以按照针迹、换色或指定的针数进行移框。
- 具备自动换色，自动剪线功能，电机自动勾线，自动断线检测。
- 高速机头，故障率极低，寿命长，噪音低，质量稳定可靠。
- 引线LED照明，实时观测绣做情况更敞亮方便。
- 带面线夹持装置，防止脱线，断线、绣品出色。
- 新型悬浮式结构绣框，型材强度更高，耐久不变形，线迹美观。
- 新型台板，坚硬度强，耐磨度高。

### Application

Ideal for high-end customization in apparel, bags, footwear, hats, toys, home decoration, and automotive interiors.

### Features

- Advanced Computer Control System with a 15.6-inch LCD touchscreen, featuring a 50ms refresh rate for real-time dynamic display. User-friendly interface with responsive touch control and large storage capacity ensures high-precision operation.
- Large Memory Capacity – Standard system storage supports up to 130 million stitches.
- Pattern Rotation & Proportional Scaling – Adjust patterns in 1% increments (50%-200% scaling) and rotate in 1° increments (0°-89°).
- Power Failure Protection – Automatically resumes embroidery from the last paused state after sudden power loss.
- Pattern Editing Functions – Rotate, scale, copy, delete, and edit designs. Supports software-based stitch limits and optional special embroidery functions (sequins, cord embroidery, beadwork, laser cutting, etc.).
- Frame Movement Control – Move the frame by stitch, color change, or specified stitch count via dedicated forward/reverse frame buttons.
- Automated Functions – Automatic color change, thread trimming, hooking thread, and thread breakage detection.
- High-speed machine head - Features an exceptionally low failure rate, extended service life, quiet operation, and consistently stable, reliable performance.
- LED Threading Light - Provides bright, focused illumination for threading the needle and allows for clear, real-time monitoring of the embroidery process, making operation more convenient and efficient.
- Thread Clamping Device – Prevents thread slippage, breakage, and ensures consistent embroidery quality.
- Features a newly designed floating structure with enhanced frame strength, ensuring long-lasting durability and resistance to deformation. This design delivers consistently beautiful and precise stitching results.
- Enhanced Worktable – High rigidity and superior wear resistance for long-term stability.

## 906电脑平绣机 906 Flat Embroidery Machine



### 主要参数 Parameters

|                                                                   |                                                                                                                        |
|-------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| 型号: GACE-NM-FE-6-300(600+40)x680-<br>Model: B-F9-VR1-NA-1P220     | 头数: 6<br>Head:                                                                                                         |
| 针数: 6/9/12/15<br>Needle:                                          | 刺绣面积: 640mm×680mm<br>Emb.Area:                                                                                         |
| 剪线方式: 动态/静态剪线<br>Thread Trimming: Dynamic/Static Thread Trimming  | 锁头方式: 电磁铁/电机锁头<br>Head Locking: Electromagnet/Motor Locking Head                                                       |
| 换色方式: 电机丝杠换色<br>Color Change: Motor Drive Lead Screw Color Change | 夹线方式: 自动夹线<br>Thread Clamping: Automatic clamping                                                                      |
| 输入输出: U盘/Wifi可选<br>Input /Output: USB/WiFi (Optional)             | 最高储存针数: 1.3亿针<br>Stitches Capacity: 130 million                                                                        |
| 电机: XY伺服电机<br>Motor: XY Servo motor                               | 过线方式: 金属中过线<br>Threading Method: Metal Threading                                                                       |
| 针步: 0.1-12.7mm<br>Stitch Length:                                  | 勾线方式: 独立/集中勾线<br>Thread Hooking: Independent/Centralized Hooking System                                                |
| 操作屏: 15.1寸触摸屏<br>Operation Screen: 15.1-inch Touch Screen         | 凸轮 (可选): 双凸轮双驱动/双凸三连杆<br>Cam (Optional): Dual-Cam Dual-Drive / Dual-Cam Three-Link Mechanism                           |
| 旋梭 (可选):<br>Rotary Hook (Optional):                               | 日本佐文或日本广濑<br>Koban or Hirose (Japan)                                                                                   |
| 外型尺寸: 3630mm×1860mm×1650mm<br>Packing Size:                       | 净重/毛重: 1600kg<br>N.W/G.W :                                                                                             |
| 功率: 4.5kW<br>Power:                                               | 输入电源: 单相220v/50Hz, 三相380v/50Hz(特殊电源可定制)<br>Power Supply: 1P 220V/50Hz, 3P 380V/50Hz (special power supply is possible) |

### 天津再登高智能制造有限公司

地址: 天津宝坻经济开发区天宝南环路3号B楼  
邮箱: sales@getonagain.com  
网址: www.GetonAgain.com

**400-166-8581**

### Tianjin GetonAgain SM Co., Ltd.

Address: Block B, No.3, Nan Huan Road, Economic Development Zone,  
Baodi, Tianjin, China. **0086-22-6035 9933**  
Email: sales@getonagain.com www.GetonAgain.com

20250603