再登高™
GetonAgain®

连续送料龙门式单针绗缝机
Continuous Feeding Gantry-Type Single-Needle Quilting Machine

适用范围

床垫、被芯、毛毯、床垫保护垫、家具软包等产品的单针花型的全自动绗缝。

Application

Suitable for the single needle quilting patterns of mattress, quilt, blanket, mattress protector, bed cover, etc.

机器特点

• 整机工作流程：自动送料、拉料、绗缝、裁切，全自动一体化完成。

• 自主研发再登高电脑控制系统，友好的人机界面，触控灵活，存储量大，确保整机的高精度运行。

• 采用绗缝专用升降式机头，升降高度可达100mm，满足不同厚度的绗缝，最高速度3000转/分钟。

• 自动雾化供油系统,有效润滑机头内零部件,延长机器使用寿命。

• 强大专业的电脑绗缝功能：如针步选择，花样缩放，花样调整等。

• 具有自动剪底面线功能，底线计数功能。

• 具有面线断线检测功能，断线后自动回穿线位并报警停车。

• 自动补缝功能，快进、快退功能；花型预览、产量统计功能。

• 原装进口2倍大旋梭，无需频繁更换底线。

• 全伺服电机驱动，绗缝精度更高。

Features

• Fully automated workflow: automatic feeding, material pulling, quilting, and cutting, all completed in one integrated process.

• Proprietary GetonAgain computer control system with user-friendly interface, flexible touch operation, and large storage capacity, ensuring high-precision machine performance.

• Specially designed lift-type quilting head with a lifting height up to 100mm, suitable for quilting materials of various thicknesses; maximum speed of 3,000 rpm.

• Automatic atomizing lubrication system effectively lubricates internal components of the quilting head, extending machine lifespan.

• Powerful and professional quilting functions: stitch selection, pattern scaling, pattern adjustment, and more.

• Features automatic upper thread / bottom thread trimming and bobbin thread counting.

• Equipped with upper thread breakage detection; machine automatically returns to threading position and stops with alarm when thread breaks.

• Automatic repair stitching, fast forward/rewind, pattern preview, and production statistics functions.

• Internation brand double-capacity rotary hook reduces the frequency of bobbin changes.

• Full servo motor drive for higher quilting precision.

连续送料龙门式绗缝机
Continuous Feeding Gantry-Type Single-Needle Quilting Machine

推荐型号 Models

推荐型号 Models	工作面积 Working Area	适用辅料宽度 Width of Fabric	占地尺寸（长×宽×高） Installation size (L×W×H)
GOA-QP,NM-CSF-1-2300×2500-SDM-LS50-VR2-TC,SL-3P380	2300mm×2500mm	1300mm-2600mm	10500mm×4600mm×1800mm
GOA-QP,NM-CSF-1-2600×2800-SDM-LS50-VR2-TC,SL-3P380	2600mm×2800mm	1600mm-2900mm	10800mm×4900mm×1800mm
GOA-QP,NM-CSF-1-3200×3200-SDM-LS50-VR2-TC,SL-3P380	3200mm×3200mm	2200mm-3500mm	11400mm×5300mm×1800mm

机器参数 Parameters

最高转速： Max. Speed:	3000 rpm	最大绗缝厚度： Max. Quilting Thickness：	50 mm	针步： Stitch Length:	2mm - 6mm
气压： Air Pressure:	0.6~0.8 MPa	额定功率： Power:	8 KW	电源电压： Power Supply:	三相380V/220V, 50Hz

机器配置 Configuration

（以下配置仅供参考，设备最终配置以制造商出厂标准为准）
（Below are for reference, pls. consult with GetonAgain for the final configurations）

15寸全触摸控制屏，
ARM工控板，LINUX系统内核，
操作简单，工作稳定。
15-inch full touchscreen control panel,ARM industrial control board, Linux OS,Easy operation and stable performance.


绗缝专用高速升降式机头

Specially designed lift-type quilting head

拖链结构，结实耐用，使用寿命长。

Drag chain structure is robust and durable, ensuring a long service life

原装进口2倍大旋梭

Internation brand double-capacity rotary hook

自动裁切箱-标配横切装置，
可选配竖切装置。
Automatic cutting box – standard with cross-cutting device,optional longitudinal cutting device available.


全伺服电机驱动，
绗缝精度更高
Full servo motor drive for higher quilting precision.

选配：红外保护功能

Optional: Infrared safety protection.

选配：智能绗缝打版软件，
可自由设计，编辑，模拟绗缝等
Optional: Intelligent quilting pattern software for freely design, editing, and quilting simulation.quilting, etc.